

# MORGAN LDX

## DESIGN INSPIRES

It transforms raw materials into emotion, styling into energy, and technology into intuition. Design has the power to transform the delivery experience. Design has guided us to create a product that goes beyond performance, precision and refinement. Design has created the Morgan LDX!



Options Shown



## STANDARD FEATURES

### SUBFRAME ASSEMBLY

- 4" Steel I-Beam Longrails
- 3" Steel I-Beam Crossmembers on 16" Centers

### FLOORING

Pine Flooring

### SIDEWALL ASSEMBLY

- .040" White Aluminum Skins
- Steel Z-Posts on 16" Centers

### FRONT END ASSEMBLY

- .040" White Aluminum Skins
- "R2" Integrated Corner Radius
  - 2" Extruded Aluminum Vertical Radii
  - 2" Extruded Aluminum Top Radius with Cast Aluminum Corners

### REAR FRAME ASSEMBLY

- Header Design with Rain Channel
- Painted (white) galvanized Rear Frame
- Curbside and Roadside Grab Handles

### REAR DOOR

Overhead Roll-up Door

### BUMPER

Bolt-On Black 10" Pooched Step Bumper

### ROOF ASSEMBLY

- .032" Aluminum Sheet
- Anti-Snag, Low Profile Roof Bows on 24" Centers

### LIGHTING

- Incandescent Exterior Lights to FMVSS108 Specifications
- Single Interior Dome Light with Switch in Cab



"R2" Corner Radius & Front-End Design, shown with optional LED lights.



Our subframe, floor under-coating and unique mounting process, have set the industry standard.



Bolt-On, Black 10" Step Bumper

## OPTIONS

### FLOORING

1 1/8" Laminated Hardwood

### BUMPER

5" Pooched Channel Bolt-On Underride ICC Bumper

### ROOF ASSEMBLY

.062" Translucent Fiberglass Roof

### LIGHTING & REFLECTORS

- LED Exterior Lights to FMVSS108 Specifications
- 1 additional Interior Dome Light on Same Switch
- Conspicuity Tape on Sides/Rear

### WALKRAMPS

Availability Dependent on Body Length/Chassis Frame Width

### LIFTGATE

#### Bolt-On Tommygate Original Series Railgate

- 91-1050 1000 lb Capacity\*
- 91-1350 1300 lb Capacity\*
- 91-1650 1600 lb Capacity\*

*\*See Tommygate Specifications for Platform Sizes*



5" pooched underride bolt-on ICC bumper



Translucent roof - allows natural lighting to brighten cargo area.





## CARGO CONTROL

### Sidewall E-Track

#### Maximum 2 Rows Surface Mounted

Standard Settings

• 24" and 48" • 30" and 60"

Optional Settings Starting at 18" Center to floor on 6" Increments

### Frontwall E-Track

#### Maximum 2 Rows Surface Mounted

Standard Settings

• 24" and 48" • 30" and 60"

Optional Settings Starting at 18" Center to floor on 6" Increments

### Tie Rings

#### Sidewall

3 per Side Surface Mounted on Plywood at 42" from Floor

#### Frontwall

2 Surface Mounted on Plywood at 42" from Floor



Cargo Area - Plywood liner, apitong scuff & e-track



Cargo Area - Slat line

## INTERIOR LINER & SCUFF - PLYWOOD

### Frontwall

- 5.2mm Luaun x 48" High
- 5.2mm Luaun x Full Height

*Optional 10 1/2" Apitong Scuff Over Luaun*

- 3/8" Plywood x 48" High
- 3/8" Plywood x Full Height

*Optional 10 1/2" Apitong Scuff Over Plywood*

- 1/2" Plywood x 48" High
- 1/2" Plywood x Full Height

*Optional 10 1/2" Apitong Scuff Over Plywood*

### Sidewall

- 5.2mm Luaun x 48" High
- 5.2mm Luaun x Full Height

*Optional 10 1/2" Apitong Scuff Over Luaun*

*plywood liner sidewall cont.*

- 3/8" Plywood x 48" High
- 3/8" Plywood x Full Height

*Optional 10 1/2" Apitong Scuff Over Plywood*

## INTERIOR LINER & SCUFF - SLAT

### Front Wall

#### 79"- 85" High Bodies

- 5 Slats Evenly Spaced
- 10 1/2" Apitong Scuff

#### 91"- 97" High Bodies

- 6 Slats Evenly Spaced
- 10 1/2" Apitong Scuff

### Sidewall

#### 79"- 85" High Bodies

- 5 Slats Evenly Spaced
- 10 1/2" Apitong Scuff

#### 91"- 97" High Bodies

- 6 Slats Evenly Spaced
- 10 1/2" Apitong Scuff



er & apitong scuff



Cargo Area - Plywood liner, apitong scuff & tie rings

## DIMENSIONAL DATA

Height & Width**				
Model	Overall Width	Interior Width	Exterior Height	Interior Height
LDX-79	96"	92 - 7/8"	85 - 3/8"	79 - 1/8"
LDX-85	96"	92 - 7/8"	91 - 3/8"	85 - 1/8"
LDX-91	96"	92 - 7/8"	97 - 3/8"	91 - 1/8"
LDX-97	96"	92 - 7/8"	103 - 3/8"	97 - 1/8"

Length**		
Model	Exterior Length	Interior Length*
10'	10' 6 1/2"	10'
12'	12' 6 1/2"	12'
14'	14' 6 1/2"	14'
16'	16' 6 1/2"	16'
18'	18' 6 1/2"	18'

\*inside front wall to inside rear door panel

Rear Roll-up Door Opening**		
Model	Opening Width	Opening Height
LDX-79	88"	73"
LDX-85	88"	79"
LDX-91	88"	85"
LDX-97	88"	91"

Calculated Weight Chart**					
Model	10'	12'	14"	16"	18"
LDX-79	1506	1717	2030	2244	2580
LDX-85	1545	1758	2076	2291	2647
LDX-91	1583	1800	2122	2339	2714
LDX-97	**	**	**	2386	2781

\*Assumes mounted body with 3/8" side liner, 1/2" front liner, 1-3/8" pine flooring and a bolt-on step bumper

\*\*Note: All dimensions, weights and measurements specified herein are subject to change without notice and may vary depending on options selected. Please contact Morgan for measurements for your particular truck body and chassis specification.

[www.morgancorp.com](http://www.morgancorp.com)



TOLL FREE: 800.666.7426

Authorized Morgan Distributor

©Morgan Corporation

At Morgan Corporation, our quest for quality and safety is ongoing and therefore the specifications on the products described herein may vary over time. Please contact us or your Authorized Morgan Distributor for the latest product information and available safety features and options.

